

### Integra One

An all-in-one thermal inkjet printer, offering incredible reliably high-quality prints, within an unbelievably compact shell



### X1 Jet

The entry level model, ideal for autocodes, combined in to one powerful, single unit that is extremely compact and cost-effective



### X Series

Our most intelligent model with separate controller, capable of controlling up to 4 printheads



### Quadro Series

For complete production integration - control up to 8 individual printheads simultaneously



Text (from 1.0mm), barcode (1D & 2D) and graphic coding	✓	✓	✓	✓
GS1 code / serialisation	✓	✓	✓	✓
Variable coding	✓	✓	✓	✓
Service-free technology	✓	✓	✓	✓
Max print height	12.7mm	12.7mm	50.8mm	101.6mm
Max layout length	6 meters	4 meters	3 meters	3 meters
Print orientation	Any	Any	Any	Any
Production speed	For varying and constant speeds, max 180m/min	For varying and constant speeds, max 90m/min	For varying and constant speeds, max 180m/min	For varying and constant speeds, max 240m/min
Max print quality	900 dpi	900 dpi	900 dpi	900 dpi
Printheads per controller	1 embedded printhead	1 embedded printhead	Up to 4 synchronised printheads for greater message height, or up to 2 independent printheads in different positions	Up to 8 synchronised printheads for greater message height, or up to 4 independent printheads in different positions
User interface	Integrated BW OLED display, iWheel control	Integrated 3-button operation with optional external OLED HMI	External 5.7" touch screen and keyboard	External BW OLED display on Quadro only
Inks for porous and non-porous materials in a range of colours	✓	✓	✓	✓
SmartCard	✓	✓	✓	✓
Printhead dimensions (L x W x H) & Weight	186 x 86 x 98mm (0.7kg)	118 x 75 x 95mm (0.6kg)	194 x 68 x 99mm (0.7kg)	194 x 68 x 99mm (0.7kg)
Controller dimensions (L x W x H) & Weight	-	120 x 88 x 20mm	Up to 140 x 220 x 230mm (3.4kg)	Up to 180 x 354 x 110mm (5.1kg)
Communication	Ethernet, EIA 232, USB-C, Wi-Fi	Ethernet, EIA 232, USB, Wi-Fi	Ethernet, EIA 232, USB	Ethernet, EIA 232, USB
IP rating	IP40	IP40	IP40	IP40
Warranty	12 months	12 months	12 months	12 months
	<a href="#">View product</a>	<a href="#">View product</a>	<a href="#">View product</a>	<a href="#">View product</a>